
Easily pinpoints bearing and machine noise

SKF Electronic Stethoscope TMST 3

The SKF TMST 3 is a high quality instrument enabling the determination of troublesome machine parts by the detection of machine noises. TMST 3 includes a headset, two different length probes (70 and 220 mm) and a pre-recorded audio CD demonstrating the most common encountered troublesome machine noises, all supplied complete in a sturdy carrying case.

- User friendly and easy to operate, no special training required.
- Lightweight ergonomic design makes it easy to operate with one hand.
- Excellent sound quality helps to reliably identify the possible cause of the noise.
- Excellent quality headset for optimum sound quality even in very highnoise environments.
- Pre-recorded demonstration CD and output for analogue recording help facilitate analysis and comparison.
- Supplied with two probes, 70 and 220 mm (2.8 and 8.7 in.) long.
- Adjustable digital volume control up to 32 levels to reach desired volume.







ЗАО "Берг АБ" (495) 727-22-72 promshop-biz@ya.ru www.promshop.biz



Technical data TMST 3 Designation Frequency range 30 Hz-15 kHz Operating temperature -10 to +45 °C (14 to 113 °F) Output volume Adjustable in 32 levels Power on Led indicator Sound volume Battery low 250 mV Maximum recorder output Headset 48 ohm (with ear defender) Auto switch off Yes, after 2 min.

Battery	4 × AAA Alkaline type IEC LR03 (included)
Battery lifetime	30 hours (continuous use)
Dimensions handset	$220 \times 40 \times 40 \text{ mm} (8.6 \times 1.6 \times 1.6 \text{ in.})$
Probe length	70 and 220 mm (2.8 and 8.7 in.)
Case dimensions	$360 \times 260 \times 115 \text{ mm } (14.2 \times 10.2 \times 4.5 \text{ in.})$
Weight Total weight Instrument Headset	1 600 g (3.5 lb) 162 g (0.35 lb) 250 g (0.55 lb)

® SKF is a registered trademark of the SKF Group.

© SKF Group 2014

The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless prior written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising out of the use of the information contained herein.

