

Grease gun 1077600 and 1077600 H

Application

Hand operated grease pump according to DIN 1283 for loose grease (ca. 500 cm³) or grease cartridge DIN 1284. The nozzle is suitable for nipples according to DIN 71412.

Description

The grease gun is delivered with a 175 mm (7 in) extension pipe with a hydraulic gripping nozzle. The grease gun 1077600 H is delivered with a with 300 mm (12 inch) high pressure hose with a hydraulic gripping nozzle. A flexible, 500 mm (20 in) long pressure hose with hydraulic gripping nozzle is available as an accessory under the designation of 1077601.



Technical data

Designation	1077600 and 1077600 H
Maximum pressure	40 MPa (5,800 psi)
Volume/stroke	Approx. 1,5 cm ³ (0.092 in ³)
Length	380 mm (15 in)
Weight	1,5 kg (3.3 lb)

Grease gun set 1077600/SET

Application

Hand operated grease gun according to DIN 1283 for loose grease (ca. 500 cm³ / 17 fl. oz.) or grease cartridges according to DIN 1284. With the various standard accessories it is suitable for both standard nipples (according to DIN 71412), flat-head grease fittings (Ø 16 mm) and other non-standardised filling points.

Description

The SKF 1077600/SET contains the following equipment:

- 1077600 grease gun
- Extension pipe with 4 jaw hydraulic nozzle
- Snap-on high pressure hose with 4 jaw hydraulic nozzle
- Snap-on extension pipe with cardan nozzle
- Snap-on extension pipe with hook-on coupler for flat-head grease fittings (Ø 16 mm)
- Female and pointed nozzle
- Carrying case



Technical data

Designation	1077600/SET
Maximum pressure	See 1077600
Volume/stroke	See 1077600
Length	See 1077600
Carrying case dimensions	385 x 300 x 100 mm (15.2 x 11.8 x 3.9 in)
Weight (complete)	2,3 kg (5.1 lb)

Replacement parts

Designation	Description
1077600-1	Extension pipe with nozzle
1077600-1A	Nozzle
1077600-2	Rubber piston of container
1077600-3	vent plug

Operating instructions

